



Data Sheet

GeneChip® Hybridization Oven 640

The GeneChip® Hybridization Oven 640 automates your hybridization process for GeneChip brand probe arrays. The oven provides precise temperature control to ensure successful hybridization, and cartridge rotation to provide continuous mixing. Up to 64 arrays can be processed at one time. The digital speed control display provides you with the option of selecting specific rotation speeds and to visually monitor the speed during the cycle.

Expanded Array Capacity

The oven holds up to eight probe array cartridge carriers, each carrier will hold eight arrays, allowing you to process as many as 64 arrays at one time.

Improved Temperature Performance

Precise temperature control is delivered as the cartridges are rotated to ensure consistent performance across your experiments.

Removable Array Carriers

The removable cartridge carrier allows you to add or remove sets of cartridges without interrupting the entire cycle and to easily transfer the cartridges to other GeneChip instruments. The carriers are color-coded for convenience.

Digital Speed Control Display

The rotation speed can be selected and visually monitored during operation with

the easy-to-read digital speed control display, allowing you to optimize your hybridizations.

System Reliability

The Hybridization Oven 640 has undergone extensive design and quality steps in order to ensure the most consistent and reliable performance. The Hybridization Oven 640 extends the Affymetrix reputation of commitment to quality.

Safety

The oven is equipped with an interlocking door for safety when operating and removing or adding cartridges during operation. The oven will automatically stop rotation when the interlock is triggered.

Dual Voltage Option

The oven is available in a 110V and 220V model, both models meet the CSA standard for North America and the LVD and EMC for the European Union.

Specifications

Dimensions:	19"H (48cm) x 18"W (46cm) x 15 D (38cm)
Weight:	50 pounds (22.7 kg)
Power Requirements:	Input Voltage — 90V-132V@47Hz-65Hz (110V) 190V-264V@47Hz-65Hz (220V) Input Power — Less than 1000 VA (110V, 220V)
Environment Requirements:	Operating Temperature Range — 15°C to 30°C Operating Humidity Range — 15% to 85% Relative Humidity
Performance Requirements:	Carousel Rotation Speed — 0-80 RPM Oven Set Point Range — Ambient + 5°C to 70°C Oven Temperature Precision — -0.4°C at Calibration Set Point Oven Temperature Accuracy — -2.0°C from display temperature over range of 30°C to 60°C
Regulatory Requirements:	Meets CSA standards for North America Meets applicable IEC standards for safety Meets applicable directives (LVD and EMC) for the European Union CE Mark (EN 61000-4-4:EFT/B, EN 61010-1: Low voltage)

Ordering Information

GeneChip® Hybridization Oven 640

- 800138** GeneChip Hybridization Oven 640 (110V) includes 4 probe array carriers
- 800139** GeneChip Hybridization Oven 640 (220V) includes 4 probe array carriers
- 200289** GeneChip Probe Array Carriers Red (quantity 2)
- 200290** GeneChip Probe Array Carriers Green (quantity 2)
- 200291** GeneChip Probe Array Carriers Purple (quantity 2)
- 200292** GeneChip Probe Array Carriers White (quantity 2)

To Order

North America

888-DNACHIP 888-362-2447

Europe

+44 (0) 1628 552550

Japan

+81-(0)3-5730-8200

AFFYMETRIX, INC.

3380 Central Expressway
Santa Clara, CA 95051 USA
Tel: 1-888-DNA-CHIP (1-888-362-2447)
Fax: 1-408-731-5441
sales@affymetrix.com
support@affymetrix.com

AFFYMETRIX UK Ltd

Voyager, Mercury Park,
Wycombe Lane, Wooburn Green,
High Wycombe HP10 0HH
United Kingdom
Tel: +44 (0) 1628 552550
Fax: +44 (0) 1628 552585
saleseurope@affymetrix.com
supporteurope@affymetrix.com


AFFYMETRIX JAPAN K.K.

Mita NN Bldg., 16 F
4-1-23 Shiba, Minato-ku,
Tokyo 108-0014 Japan
Tel: +81-(0)3-5730-8200
Fax: +81-(0)3-5730-8201
salesjapan@affymetrix.com
supportjapan@affymetrix.com

www.affymetrix.com

**For research use only. Not for use in diagnostic procedures.
Compliant with directive 2002/96/EC (WEEE)**

Part No. 700317 Rev. 3

©1999-2005 Affymetrix, Inc. All rights reserved. Affymetrix®, , GeneChip®, HuSNP®, GenFlex®, Flying Objective™, CustomExpress®, CustomSeq™, NetAffx™, Tools To Take You As Far As Your Vision®, and The Way Ahead™ are trademarks of Affymetrix, Inc. Products may be covered by one or more of the following patents: U.S. Patent Nos. 6,050,719 6,386,749; 6,705,754; and other U.S. or foreign patents.