



Dimensions are inches unless otherwise noted.

Model	Working Capacity (ft ³) [1]	Total Volume (ft ³)	HP [2]	RPM [3]	Drive Type [4]	A	B	C	D	E	F	G	H	I	J	K	L	M	N	shipping weight (lbs.)
RCB - 0.13	0.13	0.2	0.25	36	C	9	3	4	n/a	5	4	22	31	16	18	na	na	28	4	70
RCB - 0.33	0.33	0.5	0.25	28	C	12	4	4	n/a	7	6	24	35	20	19	na	na	36	4	80
RCB - 1.1	1.1	1.7	0.25	23	B/C	18	6	6	6	11	14	32	49	28	18	8	25	49	18	250
RCB - 2.5	2.5	3.9	0.5	20	B/C	24	8	8	6	14	19	37	59	38	18	10	31	58	18	330
RCB - 5	5	7.7	0.75	18	B/C	30	10	10	6	18	23	41	69	46	18	12	38	66	18	500
RCB - 8.8	8.8	13.5	1.5	16	B/C	36	11	10	6	22	27	45	77	53	18	12	45	73	18	650
RCB - 11	11	16.9	1.5	16	B/C	39	12	14	6	23	29	47	84	57	24	12	49	81	3	1,075
RCB - 14	13.7	21	2	16	B/C	42	13	16	6	24	31	49	89	61	24	12	52	84	3	1,500
RCB - 21	21	32	3	14	A	48	16	16	6	29	35	38	83	70	30	12	60	100	3	2,000
RCB - 29	29	45	5	13	A	54	18	16	8	33	40	43	92	80	36	15	67	112	3	2,500
RCB - 40	40	62	7.5	12	A	60	20	16	8	37	44	47	100	88	36	15	74	118	3	3,000
RCB - 54	54	83	10	11	A	66	21	16	10	40	49	52	108	97	42	15	80	128	3	3,600
RCB - 70	70	108	10	11	A	72	22	16	10	44	52	55	115	104	42	15	88	137	3	4,100
RCB - 89	89	137	15	10	A	78	24	16	10	48	56	59	123	112	48	15	94	145	3	4,900
RCB - 112	112	172	20	10	A	84	25	18	12	51	61	64	133	121	48	18	103	158	3	5,800
RCB - 137	137	210	35	9	A	90	27	18	12	55	65	68	141	129	54	18	109	169	3	6,600
RCB - 166	166	255	30	9	A	96	28	18	12	58	68	71	147	136	54	24	115	178	3	7,500
RCB - 198	198	305	40	9	A	102	30	18	12	62	72	75	155	144	60	24	121	187	3	8,550
RCB - 237	237	365	40	8	A	108	32	18	12	66	76	79	163	152	60	30	131	205	3	9,600
RCB - 277	277	426	50	8	A	114	33	18	12	70	80	83	171	159	66	30	138	212	3	10,550
RCB - 325	325	500	60	8	A	120	37	18	12	75	85	88	181	169	72	30	144	218	3	11,500

Dimensions and capacities are approximate and subject to change. Do not use for installation.

[1] Working capacity is 65% of total volume.

[2] Horsepower is based on bulk density of 100 lbs./ft³ and natural angel of repose of 45°.

[3] Rotational speed can be changed based on product characteristics.

[4] Standard drive: A = gear & pinion, B = chain & sprockets, C = hollow-bore (optional on most models)

Talk with the Experts

phone 630.350.3012
sales@pauloabbe.com

fax 630.238.7584
www.pauloabbe.com