

THERMISTOR TEMPERATURE VS RESISTANCE

PART NUMBERS 290137& 290138

2252 ohms @ 25c

DEG C	OHMS	DEG C	OHMS	DEG C	OHMS	DEG C	OHMS
-80	1660C	-40	75.79K	0	7355	40	1200
-79	1518K	-39	70.93K	1	6989	41	1152
-78	1390K	-38	66.41K	2	6644	42	1107
-77	1273K	-37	62.21K	3	6319	43	1064
-76	1167K	-36	58.30K	4	6011	44	1023
-75	1071K	-35	54.66K	5	5719	45	983.8
-74	982.8K	-34	51.27K	6	5444	46	946.2
-73	902.7K	-33	48.11K	7	5183	47	910.2
-72	829.7K	-32	45.17K	8	4937	48	875.8
-71	763.1K	-31	42.42K	9	4703	49	842.8
-70	702.3K	-30	39.86K	10	4482	50	811.3
-69	646.7K	-29	37.47K	11	4273	51	781.1
-68	595.9K	-28	35.24K	12	4074	52	752.2
-67	549.4K	-27	33.15K	13	3886	53	724.5
-66	506.9K	-26	31.20K	14	3708	54	697.9
-65	467.9K	-25	29.38K	15	3539	55	672.5
-64	432.2K	-24	27.67K	16	3378	56	648.1
-63	399.5K	-23	26.07K	17	3226	57	624.8
-62	369.4K	-22	24.58K	18	3081	58	602.4
-61	341.8K	-21	23.18K	19	2944	59	580.9
-60	316.5K	-20	21.87K	20	2814	60	560.3
-59	293.2K	-19	20.64K	21	2690	61	540.5
-58	271.7K	-18	19.48K	22	2572	62	521.5
-57	252K	-17	18.40K	23	2460	63	503.3
-56	233.8K	-16	17.39K	24	2354	64	485.8
-55	217.1K	-15	16.43K	25	2252	65	469
-54	201.7K	-14	15.54K	26	2156	66	452.9
-53	187.4K	-13	14.70K	27	2064	67	437.4
-52	174.3K	-12	13.91K	28	1977	68	422.5
-51	162.2K	-11	13.16K	29	1894	69	408.2
-50	151K	-10	12.46K	30	1815	70	394.5
-49	140.6K	-9	11.81K	31	1739	71	381.2
-48	131K	-8	11.19K	32	1667	72	368.5
-47	122.1K	-7	10.60K	33	1599	73	356.2
-46	113.9K	-6	10.05K	34	1533	74	344.5
-45	106.3K	-5	9534	35	1471	75	333.1
-44	99.26K	-4	9046	36	1412	76	322.3
-43	92.72K	-3	8586	37	1355	77	311.8
-42	86.65K	-2	8151	38	1301	78	301.7
-41	81.02K	-1	7741	39	1249	79	292
						80	282.7